



KNITTING PATTERN

Gaja

Slipover

Design: MZ Design | Hobbii Design

MATERIALS

3 (3) 3 (4) skeins of Honey Bunny Shine,
Color caramel (14)

Circular needles 6 mm, 80 cm
Circular needles 8 mm, 80 cm
Stitch markers
Clover Wonder Clips
Wool needle

YARN QUALITY

 **Honey Bunny Shine**, Hobbii
100% Polyester
100 g (3.5 oz) = 120 m (131 yds)

GAUGE

10 x 10 cm (4" x 4") = 9 sts x 14 rows

ABBREVIATIONS

K = knit
P = purl
St(s) = stitch(es)
sel = selvage
R = row(s)
RS = right Side
WS = wrong side

SIZE

S (M) L (XL)

MEASUREMENTS

Length: 60 (64) 66 (66) cm/23.6 (25.2) 26 (26) inches
Width: 45 (49) 54 (60) cm/17.7 (19.3) 21.3 (23.6) inches

PATTERN INFORMATION

This gorgeous Gaja Slipover is perfect for the mild autumn days. The pattern is beginner friendly, and the slipover is worked in two parts which are joined at the shoulders. The sides are open, just tied with two ties in each side. It works up quickly due to the large needles.

Only knit and purl stitches are used, and the pattern comes with a picture guide.

This pattern can also be found in a children's version.

HASHTAGS FOR SOCIAL MEDIA

#hobbiidesign #hobbiigaja "hobbiielements

BUY THE YARN HERE

<https://shop.hobbii.com/gaja-slipover>



QUESTIONS

If you have any questions regarding this pattern, please feel free to email us at support@hobbii.com

Please make sure to include the pattern's name and number.

Happy Crafting!

Pattern



TIPS AND INFO

In this pattern only knit and purl stitches are used, making it a very beginner-friendly project.

You can cast on as you prefer, but I find the cable-on-cast-on easier to use for this yarn. See pictures below. I recommend using needles one or two sizes bigger than the ones for knitting to keep the cast-on edge from being too tight.

The slipover is designed to be open at the sides, but the width can easily be adjusted to make a closed version. Just use your own measurements to find the correct width. If for instance, you want it to be 5 cm/2" wider, you will calculate it like this: 10 cm (4") = 9 sts, 1 cm (0.4") = 0.9 sts, 5 cm = 5 x 0.9 = 4.5. meaning you will add 5 sts to the width. I recommend closing the sides by slip stitching them together, but you can use your preferred method.

When working with chenille yarn, it is recommended to tie a knot in all ends and to only sew short lengths to keep the yarn from fraying.

Cable cast-on: wrap the yarn around the needle to create a loop, repeat to get two loops. Insert the right-hand needle between the two loops, yarn over and pull through. Move this new loop onto the left-hand needle (see pictures 1-3 below). Repeat until you have the desired stitch number.

Selvage (sel): knit the first stitch on row, slip the last stitch purlwise (with yarn in front).

BACK PANEL

Cast on 50 (55) 60 (67) sts using the cable cast-on or your preferred method. Work flat.

Work 5 rows of garter stitch (knit all rows), 1. Row will be a WS-row. Then:

Row 1 (RS-row): sel, knit until last st, sel

Row 2 (WS-row): sel, knit 4, place stitch marker, p until 5 sts remain, place stitch marker, k 4, sel (see picture 4).

Repeat these 2 rows until you have the desired length minus 3 cm/1.2 inches.

Neck opening

Place a stitch marker after 12 (14) 16 (20) sts (shoulder stitches), count another 26 (27) 28 (27) sts (neck opening) and place a stitch marker, you will then have 12 (14) 16 (20) sts for the other shoulder. NOTE: if you have your slip-over wider, you will keep the same number of sts for the neck opening as instructed, unless you prefer a wider or narrower neck opening.

Row 1 (WS-row): sel, k 4, p 7 (9) 11 (15), k 26 (27) 28 (27), p 7 (9) 11 (15), k 4, sel

Row 2 (RS-row) sel, knit all sts, sel

Repeat these 2 rows until you have worked a total of 5 rows.

Bind off loosely from the RS.

FRONT PANEL

Is worked the same as back panel.

TIE-STRINGS (MAKE 8)

Cast on 5 sts and work flat: *sel, k 3, sel* until 30 cm/12 inches or desired length. NOTE: the tie-string will expand, so be sure to stretch it a little when measuring.

Bind off keeping a long tail for attaching the tie-string to the slip-over.

FINISHING

Place both parts with RS facing and sew the shoulder seams from the armholes to the marked stitches. Turn work with RS out. Place a Clover Clip 21 (22) 23 (23) cm measured from the shoulder seam on each side (for the sleeve) of both front and back panel (see picture 6) and again 20 (21) 22 (22) cm further down (or at desired length, you will want the ties at or just below your waist). Try on the slip-over to make sure the ties are places as you like.

Place a tie on the RS of the slip-over at the marked places (see picture 7) and use the clips to keep them in place. Repeat for all 8 string ties. Attach them by sewing them on from the RS.

Weave in all loose ends!

Done!

Enjoy!

Marlis Zimmer



Photo guide

Cable cast-on



Picture 1



Picture 2



Picture 3

Slipover



Picture 4



Picture 5



Picture 6



Picture 7



Picture 8